



**Z3Cam<sup>TM</sup>**

*Expand Your Reach*

*H.265 and H.264 IP Video  
Camera Solutions*

[www.Z3technology.com](http://www.Z3technology.com)

# Z3Cam•DX™

## Dual Spectrum IP Camera



### Details

#### Camera Features

- 1/2.3in 4K CMOS image sensor
- Image capture up to 8.51 mega pixels
- 30x zoom in 2160p30 using Sony's patented Super Resolution zoom, 40x zoom in 1080p
- Noise reduction algorithm for high frequency and high detail areas
- Visibility enhancer ICR (Day and Night)
- High sensitivity image processor and wide dynamic range
- Leverages Sony's FCB-ER8530 4K camera module

#### Thermal Camera Features

- High contrast thermal imaging camera
- Integrated Shutter for imaging calibration
- Supports 320 x 240 resolution
- Pass Tamarisk control commands over IP via Web GUI or SSH
- Image control Wht Hot, Blk Hot, Invert Revert
- Leverages DRS Tamarisk camera module

#### Streaming Features

- H.265, H.264 or MJPEG encoded video over IP with no distance limitations
- Supports 4K UHD and HD resolutions up to 30 fps (2160p, 1080p, 720p, and lower)
- Outputs RTP, RTSP, MPEG-2 TS or RTMP\*
- Simultaneously stream and/or record in multiple resolutions and bitrates
- Compatible with Wowza Streaming Engine™\* and You Tube Live\*
- Dual Camera Streaming
- Dual monitor view optional; or visible with thermal overlay picture-in-picture mode

#### Decode

- Compatible with ZEUS® HE265-DEC (also available from Z3 Technology)
- PC decoding

### Specifications

Interfaces	Gigabit Ethernet, USB 2.0, Line Level Audio Input and Composite Video Output
Power	7.5W typical while encoding H.265 video
Mount	1/4 20 UNC tripod screw hole on bottom of unit
Dimensions	121 x 125 x 62 mm (4.8 x 4.9 x 2.4 in)
Weight	955 g (2.1 lb)

# Z3Cam·LX™

*Lowlight eXtreme H.265 4K IP Camera*



## Details

### Camera Features

- 35mm full frame CMOS sensor
- ISO 409,600/0.004 LX
- Long Exposure and High ISO noise reduction
- High sensitivity image processor
- Easily mount to gimbal or tripod, top and bottom bracket mount
- Additional composite input for dual camera set-up with dual monitoring viewing or Picture in Picture display
- Interchangeable E-mount FE lenses

### Streaming Features

- H.265, H.264 or MJPEG encoded video over IP
- Supports 4K UHD and HD resolutions up to 29.97/25 (2160p, 1080p, 720p, and lower)
- Outputs RTP, RTSP, MPEG-2 TS or RTMP\*
- Simultaneously stream and/or record in multiple resolutions and bitrates
- Supports unicast and multicast streaming

### Control

- IP Control and Configuration
- RS-485/422
- Z3 web interface
- RS-232/GPIO
- Supports ONVIF® Profile S

### Recording

Compressed USB Recording

### Decode

- Compatible with ZEUS® HE265-DEC (also available from Z3 Technology)
- PC decoding

## Specifications

### Interfaces

Gigabit Ethernet, USB 2.0, Microphone Input and Composite Output

### Power

23W typical while encoding H.265/HEVC video

### Mount

1/4 20 UNC tripod screw hole on bottom of unit, Top and Bottom bracket mount

### Dimensions

145 x 142 x 89 mm (5.7 x 5.6 x 3.5 in)

### Weight

1035 g (2 lb 28 oz)

# Z3Cam.4K™

## H.265/H.264 4K IP Video Camera

Model: Z8300



### Details

#### Camera Features

- 30x optical zoom using Sony Super Resolution Zoom feature
- Noise reduction algorithm for high frequency and high detail areas
- Visibility enhancer ICR (Day and Night)
- High sensitivity image processor
- Easily mount to tripod or mounting bracket
- Leverages Sony's FCB-ER8300 4K camera module

#### Streaming Features

- H.265, H.264 or MJPEG encoded video + AAC audio over IP with no additional equipment and no distance limitations
- Supports 4K UHD and HD resolutions up to 30 fps (2160p, 1080p, 720p, and lower)
- Outputs RTP, RTSP, MPEG-2 TS or RTMP\*
- Simultaneously stream and/or record in multiple resolutions and bitrates
- Supports unicast and multicast streaming
- Compatible with Wowza Streaming Engine™, YouTube Live and Facebook Live

#### Control

- IP Control and Configuration
- Z3 web interface
- Pass Sony VISCA™ Camera Control Commands over IP
- Supports ONVIF® Profile S with Media Services 2.0

#### Recording

Compressed USB Recording

#### Decode

- Compatible with ZEUS® HE265-DEC (also available from Z3 Technology)
- PC decoding

### Specifications

#### Interfaces

Gigabit Ethernet, USB 2.0, Audio Input and Composite Output

#### Power

7.5W typical while encoding H.265 video

#### Mount

1/4 20 UNC tripod screw hole on bottom of unit

#### Dimensions

144 x 64 x 66 mm (5.6 x 2.5 x 2.6 in)

#### Weight

818 g (1.8 lb)

# Z3Cam-4K™

## H.265/H.264 4K IP Video Camera

Model: Z8530/Z8550



### Details

Camera Features	<ul style="list-style-type: none"><li>• 30x optical zoom using Sony's Super Resolution Zoom, 40X optical zoom in 1080p30 mode using SRZ</li><li>• Genlock multiple cameras with External Sync on the Z3Cam-4K model Z8550</li><li>• Noise reduction algorithm for high frequency and high detail areas</li><li>• Visibility enhancer ICR (Day and Night)</li><li>• High sensitivity image processor</li><li>• Small 4K camera body footprint similar in size to the HD camera body</li><li>• Easily mount to tripod or mounting bracket</li></ul>
Streaming Features	<ul style="list-style-type: none"><li>• H.265, H.264 or MJPEG encoded video over IP with no additional equipment and no distance limitations</li><li>• Supports 4K UHD and HD resolutions up to 30 fps (2160p, 1080p, 720p, and lower)</li><li>• Outputs RTP, RTSP, MPEG-2 TS or RTMP*</li><li>• Simultaneously stream and/or record in multiple resolutions and bitrates</li><li>• Supports unicast and multicast streaming</li><li>• Compatible with Wowza Streaming Engine™*, Facebook Live and YouTube Live</li></ul>
Control	<ul style="list-style-type: none"><li>• Z3 web interface for control and configuration</li><li>• Pass Sony VISCA™ Camera Control Commands over IP</li><li>• Supports ONVIF® Profile S with Media Services 2.0</li></ul>
Recording	Compressed USB Recording
Decode	<ul style="list-style-type: none"><li>• Compatible with ZEUS® HE265-DEC (also available from Z3 Technology)</li><li>• PC decoding</li></ul>

### Specifications

Interfaces	Gigabit Ethernet, USB 2.0, Audio Input, Composite Output, MMCX Composite Input* and RS-485 Input*
Power	7.5W typical while encoding H.265 video
Mount	1/4 20 UNC tripod screw hole on bottom of unit
Dimensions	130 x 61 x 62 mm (5.1 x 2.4 x 2.4 in)
Weight	682 g (1.5 lb)

\*Z3Cam-4K Model Z8550 Only

# Z3Cam•HD™

H.265/H.264 HD IP Video Camera



## Details

Camera Features	<ul style="list-style-type: none"><li>• Full HD 30x optical zoom</li><li>• 2D/3D noise reduction algorithm for high frequency and high detail areas</li><li>• Visibility enhancer auto ICR (Day and Night)</li><li>• High sensitivity image processor</li><li>• Spherical privacy zone masking</li><li>• Leverages Sony's FCB-EV7520 HD camera block</li></ul>
Streaming Features	<ul style="list-style-type: none"><li>• H.265, H.264 or MJPEG encoded video + AAC audio over IP with no additional equipment and no distance limitations</li><li>• Supports HD resolutions up to 60 fps (1080p, 720p, and lower)</li><li>• Outputs RTP, RTSP, MPEG-2 TS or RTMP*</li><li>• Simultaneously stream and/or record in multiple resolutions and bitrates</li><li>• Supports unicast and multicast streaming</li><li>• Compatible with Wowza Streaming Engine™ and YouTube Live*</li></ul>
Control	<ul style="list-style-type: none"><li>• IP Control and Configuration</li><li>• Z3 web interface</li><li>• Pass Sony VISCA™ Camera Control Commands over IP</li><li>• Supports ONVIF® Profile S with Media Services 2.0</li></ul>
Recording	Compressed USB Recording
Decode	<ul style="list-style-type: none"><li>• Compatible with ZEUS® HE265-DEC (also available from Z3 Technology)</li><li>• PC decoding</li></ul>

## Specifications

Interfaces	Gigabit Ethernet, USB 2.0, Micro-HDMI Output, Audio Input and Composite Output
Power	7.5W typical while encoding H.265 video
Mount	1/4 20 UNC tripod screw hole on bottom of unit
Dimensions	128 x 62 x 62 mm (5.0 x 2.4 x 2.4 in)
Weight	650 g (1.4 lbs)

# HE265-DEC

4K Ultra HD H.265 Decoder



## Details

Interfaces	1x 4K HDMI Output 2 x 3G-SDI Output	1 x USB 2.0 1 x USB 3.0
Supported Resolutions	HD resolutions up to 2160p30 (4K UHD), 1080p30, 1080p/i at 60fps and 720p60	
Video Codecs	MPEG-2, H.265 & H.264	
Input Formats	UDP/TSRTP, SRT, RTMP, HLS, Zixi, RTSP Client	
Output Formats	UDP, RTP, SRT, RTMP Client, Zixi	
Video Frame Rates (HD)	25p, 29.97p, 30p, 50p, 59.94p and 60p @ 720p 24p, 25p, 29.97p, 30p, 50p, 59.94p and 60p @ 1080p 50i, 59.94i and 60i @ 1080i	
Video Frame Rates (UHD)	23.98p, 24p, 25p, 29.97p and 30p @ 2160p	
Closed Captions	EIA708, DUP EN on screen display 300743	
Audio Codecs	MPEGIL2, AAC-LC, Dolby Digital Passthrough	

## Specifications

Software Control	HTTP-Based GUI: Configuration and Software Update MUSB: Configuration	
Power	12VDC	
Dimensions (L x W x H)	260 x 130 x 27 mm (10.2 x 5.0 x 1.0 in)	
Weight	608 g (1.34 lb)	

# DISTRIBUTORS

## **Aegis Electronic Group, Inc.** **USA**

Phone: +1.760.729.2026  
Website: [www.aegiselect.com](http://www.aegiselect.com)

## **JMC Group** **Italy**

Website: [www.jmccomputers.it](http://www.jmccomputers.it)

## **Heartland Video Systems** **USA**

Phone: +1.800.322.7088  
Website: [www.hvs-inc.com](http://www.hvs-inc.com)

## **Phase1 Technology** **USA**

Phone: +1.631.254.2600  
Website: [www.phase1vision.com](http://www.phase1vision.com)

## **Elvitec** **France**

Phone: +33.4.90.09.25.80  
Website: [www.elvitec.fr](http://www.elvitec.fr)

## **Markertek** **USA**

Phone: +1.800.522.2025  
Website: [www.markertek.com](http://www.markertek.com)

## **Videoset** **Israel**

Phone: +972.54.2424240  
Website: [www.videoset.com](http://www.videoset.com)

# ABOUT Z3

Z<sup>3</sup> Technology is an industry-leading, USA-based manufacturer of production-ready embedded multimedia solutions and IP camera systems. From our founders to our world-class engineers to our sales and customer service team, we understand your requirements and speak your language. Our experience allows us to provide cost-effective solutions to meet your product requirements. With the assistance of our robust worldwide distribution and sales networks, we can provide a simple solution for your multimedia needs.



## **Contact Us:**

[sales@Z3technology.com](mailto:sales@Z3technology.com)  
+1.402.323.0702