

• HDMI HYPER QUICK RELEASE

Ensure portability, versatility and ease of setup, together with ability to transmit excellent video quality through HDMI integrated on the gimbal.

BUILT-IN 14.5V POWER REGULATOR (15V-52V INPUT)

Allow the motor to run 20% more powerfully.





Communicate with Pixhawk FC

AUX PORT

HDMI PORT

SBUS PORT

JR PORT

POWER PORT

USB PORT To update firmware

CAN PORT

Communicate with

CL CH 0V 5V

• UP TO 9 SIGNALS ON AUX PORT

Aux port with S1-S9 optional signals to connect to other devices such as AV signal or camera trigger.



• START-UP TIME WITHIN 2 SECONDS

No need to manually set up the home position. Plug & play installation within 2 seconds.

BUILT-IN BLUETOOTH

Allow quickly interface with multiple devices

such as FC remote control, auxiliary I/O, etc.

CONNECTION

NEW I/O DESIGN

Allow to conveniently control the gimbal via smartphone, tablet or other suitable devices.

WEIGHT & DIMENSION

 Weight
 2.65 lbs (1200 g)

 Maximum Payload
 3.7 lbs (1700 g)

CAMERA COMPATIBILITY •





Panasonic GH3, GH4, Canon 6D Mk I, Mk



Pentax



Nikon D810, D800, D500



Sony Alpha A9 (I - II)



Sony A6000, A6300, A6500



Sony A7S (mk I - II)



Sony A7r (mk I - IV)



Phase One iXM50/100



UMC-S3CA



FUJIFILM X-T

