



Helix Antenna

The compact-sized Helix antenna is designed with high stability and repeatability at phase center, and its high gain ensures a superior performance even at low elevation angle. Available from single frequency to triple frequencies, AT-series Helix antennas are optimal for Unmanned Aerial Vehicle, GIS, RTK and related mobile devices where need high accuracy GNSS positioning.

AT150 HELIX ANTENNA

- GPS L1, GLONASS L1, BeiDou B1 tracking
- Lightweight and low noise figure design
- Ground Plane independent
- High stability and repeatability at phase center
- IP65-level waterproof design

AT180 HELIX ANTENNA

- GPS L1, L2 and BeiDou B1, B2 / GLONASS L1, L2 tracking
- Compact size and low consumption design
- Multi-feed, wide beam design
- Ground Plane independent
- High stability and repeatability at phase center
- High gain with superior tracking performance

AT190 HELIX ANTENNA

- GPS L1, L2, GLONASS L1, L2, BeiDou B1, B2, B3 and Galileo E1, E5a, E5b tracking
- High gain (3.5dBi) with superior tracking performance at low elevation angle
- Compact size and low noise figure
- Ground Plane independent
- High stability and repeatability at phase center
- IP67-level waterproof design

AT-series Helix Antenna

| Characteristics | AT150 | AT180/AT180G | AT190 |
|-----------------------|--------------------------------------|---|---|
| Antenna | | | |
| Antenna Type | Helix Antenna | Helix Antenna | Helix Antenna |
| Frequency Range | GPS: L1 GLONASS: L1 BeiDou: B1 | GPS: L1, L2 BeiDou: B1, B2 (AT180) GLONASS: L1, L2 (AT180G) | GPS: L1, L2 GLONASS: L1, L2 BeiDou: B1, B2, B3 Galileo: E1, E5a, E5b |
| Impedance | 50 Ohm | 50 Ohm | 50 Ohm |
| Polarization | RHCP | RHCP | RHCP |
| Axial Ratio | ≤3dB | ≤3dB | ≤3dB |
| Azimuth Coverage | 360° | 360° | 360° |
| Noise Figure | ≤2.0 | ≤2.0 | ≤2.0 |
| Gain at Zenith | 2dBi | 2dBi | 3.5dBi |
| LNA | | | |
| LNA Gain | 33±2dB | 33±2dB | 33±2dB |
| Noise Figure | ≤2dB | ≤2dB | ≤2dB |
| VSWR Output | ≤2.0 | ≤2.0 | ≤2.0 |
| Operation Voltage | 3.3 - 12VDC | 3.3 -12VDC | 3.3 -12VDC |
| Operation Current | ≤45mA | ≤55mA | ≤45mA |
| Ripple | ±2dB | ±2dB | ±2dB |
| Physical | | | |
| Dimension | Φ27.5x59mm | Φ27.5x59mm | Φ27.5x59mm |
| Connector | SMA male connector | SMA male connector | SMA male connector |
| Weight | 19g | 19g | 25g |
| Environmental | | | |
| Operating Temperature | -40 ℃ to +85 ℃ | -40 ℃ to +85 ℃ | -40 ℃ to +85 ℃ |
| Storage Temperature | -55 ℃ to +85 ℃ | -55 ℃ to +85 ℃ | -55 ℃ to +85 ℃ |
| Humidity | 95% No-condensing | 95% No-condensing | 95% No-condensing |

© 2017, ComNav Technology Ltd. All rights reserved. **SINO GNSS** is the official trade mark of ComNav Technology Ltd., registered in People's Republic of China, EU, USA and Canada. All other trademarks are the property of their respective owners. (September 2017).

ComNav Technology Ltd.

Building 2, No. 618 Chengliu Middle Road,
201801 Shanghai, China

Tel : +86 21 64056796

Fax: +86 21 54309582

Email: sales@comnavtech.com

www.comnavtech.com

