



SPECIFICATION

MECHANICAL & ELECTRICAL CHARACTERISTICS

Working Current	Static current: 400mA (@12V)
	Dynamic current: 800mA (@12V)
	Locked motor current: Max 4.0A (@12V)
Operating Temperature	5° F ~ 120° F (-15° C ~ 50° C)
Weight	1 lb (0.465 kg)
Gimbal Dimension	112(W) x 145(D) x 200(H)


PERIPHERAL

Camera Tray Dimensions	Maximum depth from the center of gravity on camera base plate: 65.5mm
	Maximum height measured from top of camera base plate: 70mm
	Maximum width: 100mm
Input Power	14-52V
Connections	USB 2.0, CAN, UART, S-bus, Spektrum, PPM, Bluetooth
PC Assistant Software Requirements	Windows XP or above; Mac OS X 10.9 or above
Mobile Assistant Software Requirements	iOS 7.1 or above; Android 4.3 or above

WORKING PERFORMANCE

Maximum Payload	465g
Angular Vibration Range	± 0.02°
Maximum Controlled Rotation Speed	Pan axis: 100°/s
	Tilt axis: 100°/s
	Roll axis: 100°/s
Mechanical Endpoint Range	Pan axis control: +330° to -330°
	Tilt axis control: +135° to -45°
	Roll axis control: +45° to -90°
Controlled Rotation Range	Pan axis control: +330° to -330°
	Tilt axis control: +135° to -45°
	Roll axis control: ± 45°

DIMENSION & CAMERA CAGE



CAMERA COMPATIBILITY



Flir Vue Pro R



Flir Duo Pro R



Flir Vue



Sony RX100



Sony R10C



Sony QX1



Blackmagic Micro
Cinema Camera



Workswell Wiris Pro



Rededge MX

For more information, visit our website at: gremsy.com

For instant support, send us an email to contact@gremsy.com



@GREMSYTECH



FACEBOOK.COM/GREMSY



GREMSY.COM