

# SKIRON-X



## Small Unmanned Aerial System (sUAS)

### OPTIMIZED FOR SIMPLE AND EFFECTIVE ISR MISSIONS

The Skiron Expeditionary sUAS (SKIRON-X) is a Group 2 sUAS that combines the simple operation of an electric vertical take-off and landing (eVTOL) configuration with the longer range and endurance of a fixed-wing design. It has a range of up to 8 miles (12.9 km) and its EO/IR camera provides excellent ground resolution for airborne intelligence, surveillance, and reconnaissance (ISR).

### KEY FEATURES

#### Hybrid VTOL Fixed-Wing

Lift rotors enable the convenience of vertical take-off and landing, while the fixed wing design allows for longer range and endurance.

#### Simplified operations

Quick to train with user-friendly mission planning software that makes it easy to implement mission changes, even during flight. Two-person crew capable and a quick setup procedure.

#### Flexible ISR payload

Excellent ground resolution with ISR-focused EO/IR camera payload options. Modular nosecone design for quick payload swaps or custom payload integration.

#### Long-range comms

Military-grade radio enables long range and high bandwidth communications. Mesh network compatible.

#### Part 107 compliant

Flexibility to fly in more areas for operations and training. Includes anti-collision lights.

### KEY SPECIFICATIONS

<b>Length</b>	2.2 m / 7 ft 2 in
<b>Wingspan</b>	5.0 m / 16 ft 6 in
<b>System container</b>	26 in x 24 in x 94 in
<b>Takeoff weight</b> <small>(with Trillium HD55 payload and battery)</small>	22.2 kg / 49 lb
<b>Payload weight</b> <small>(Trillium HD55)</small>	1.45 kg / 3.2 lb
<b>Flight endurance (max)</b>	3 hours
<b>Hover endurance (max)</b>	25 minutes
<b>Max horizontal speed</b>	26 m/s / 50 knots
<b>Cruise speed</b>	19 m/s / 36 knots
<b>C2 Link Range</b>	12.9 km / 8 mi