



# TUALAJ 16300 - D

## CRPA GNSS Anti-Jam System

### GENERAL DESCRIPTION

TUALCOM CRPA Anti-Jam GNSS Systems support critical missions by providing jam free GNSS signals and resilient PNT.

With its 16-element CRPA antenna, state-of-art digital controller and novel beamforming techniques TUALAJ 16300-D eliminates interference to ensure uninterrupted operation of GNSS receivers in the presence of jamming sources from up to 15 different directions in 3 different frequency bands. The set of protected active bands is pre-selectable amongst available options.

TUALAJ 16300-D supports various messaging formats and integrates seamlessly with civil and military GNSS receivers deployed on land/sea platforms and fixed installations. TUALAJ 16300-D also offers embedded high performance GNSS receiver as an option and allows SBAS signals to be utilized for increased accuracy and reliability.

TUALAJ 16300-D is encapsulated in specifically designed housing to withstand the harshest environmental conditions and therefore is especially suitable for maritime platforms. In addition to CRPA, protection performance is further improved using adaptive notch filtering and pulse blanking.

### BENEFITS

- Antenna and controller integrated as a single unit.
- Protection against jammers from 15 different directions
- Easy to install
- Plug and play integration into new or legacy platforms
- Immediate availability for urgent operational needs
- Compatible with all types of external GPS receivers and vehicle navigation systems, including M Code
- Compact Size
- Superior suppression performance
- Embedded GNSS receiver option
- Compatibility with military standards
- Resilient PNT

### APPLICATION AREAS

- Naval and Coast Guard Platforms
- Armored Land Vehicles
- Maritime EW Protection
- Critical Infrastructure EW Protection
- Military Communications


# TUALAJ 16300 - D

## CRPA GNSS Anti-Jam System



### Dimensions (cm)


 Diameter: Ø30  
Height: 8

 **Weight (g)**  
4500


 **Power Consumption**  
< 25 W

 **Antenna Array**  
16 Array CRPA Antenna

 **Simultaneous Independent Nulling**  
15


 **Simultaneously Protected Active Bands**  
**Option 1**  
GPS (L1, L2), GLONASS (G1, G2), GALILEO E1, BEIDOU B1, SBAS  
**Option 2**  
GPS (L1, L2, L5), GALILEO (E1, E5a, E5b), BEIDOU B1, SBAS


 **Nominal Wideband Suppression**  
>50 dB

 **Connectors**  
2 x D38999  
1 x TNC

 **Internal GNSS Tracking Sensitivity**  
-164 dBm


 **Operating Voltage**  
18-32 Vdc

 **Operating Temperature**  
-40 °C to +85 °C

 **Embedded GNSS Receiver (Optional)**  
GPS (L1, L2), GLONASS (G1, G2), Galileo (E1, E5b), BeiDou (B11), SBAS, QZSS (L1), RTCM Support

 **Environmental Tests**  
MIL-STD-810G

 **EMI / EMC**  
MIL-STD-461F

 **Data Interfaces**  
Ethernet (Optional)  
Serial RS-232  
Serial RS-485

 **RTCM Support**  
Yes

© 2026 TUALCOM: The information contained herein is subject to change without notice. TUALCOM cannot be held responsible for this and no liability is accepted for any errors or omissions.

 TUALCOM

 [www.tualcom.com](http://www.tualcom.com)  
 [sales@tualcom.com](mailto:sales@tualcom.com)  
 +90 (312) 485 22 85



100172601